

DUS 60

Technical Specifications



Convex array: C363UA(2.0/3.0/4.0/5.0/6.0MHz)
Applications: Abdomen, OB, GYN, Urology



Micro-convex array: C321UA(2.0/3.0/4.0/5.0/6.0MHz)
Applications: Cardiac, Pediatric



Linear array: L763UA(6.0/7.0/8.0/9.0/10MHz)
Applications: Musculoskeletal, Vascular, Breast, Orthopedics



Endovaginal: E613UA(4.5/5.5/6.5/7.5/8.5MHz)
Applications: OB, GYN



Convex array: C343UA(2.0/3.0/4.0/5.0/6.0MHz)
Applications: Abdomen, OB, GYN



Micro-convex array: C613UA(4.5/5.5/6.5/7.5/8.5MHz)
Applications: Cardiac, Pediatric



Linear array: L743UA(6.0/7.0/8.0/9.0/10MHz)
Applications: Small parts



Endorectal: E743UA(6.0/7.0/8.0/9.0/10MHz)
Applications: Urology

General:

Imaging mode: B, B+B, 4B, B+M, M, and PW
Gray scales: 256
Display: 12.1" TFT-LCD
Transducer frequency: 2.0~10MHz
Transducer connector: 2 standard
Beam-forming: Digital Beam-forming
Dynamic Receiving Focusing
Real-time Dynamic Aperture
Dynamic Frequency Scanning
Dynamic Apodization
Tissue Harmonic Imaging
Tissue Specific Imaging
Scanning angle: from 30 to 155 degree (depending on transducers)
Scanning depth (mm): from 20 to 250 (depending on transducers)

Functions:

Cine loop: 256 frames bidirectional cine-loop
Zoom: $\times 1.0, \times 1.2, \times 1.4, \times 1.6, \times 2.0, \times 2.4, \times 3.0, \times 4.0$ in distance
panoramic zoom in real-time and frozen condition
Storage media: Built-in Flash, External USB-Memory stick
Built-in image archive: 504MB built-in image storage
Body mark: >80 types
Transducer auto-detection
16-segment acoustic power output adjustment

Others:

Peripheral port: Video output $\times 1$
VGA output port $\times 1$
USB port $\times 2$
DICOM3.0 $\times 1$ (optional)
Power supply: 100V-240V~50Hz/60Hz
Lithium battery: Continuous working for 2 hours
Dimensions: 330mm(W) \times 320mm(L) \times 253mm(H)
Netweight: 7.1kg

Imaging Processing:

Pre-processing: Dynamic range
Edge enhancement
Frame correlation
Line correlation
Smooth
AGC
8-segment TGC adjustment
IP (Imaging Process)
Post-processing: Gray map
Gamma correction
Rejection
Pseudo-color
Left-right reverse
Up-down reverse

Measurement & Calculation:

B-mode: distance, circumference, area, volume, ratio, stenosis%, and angle
M-mode: distance, time, slope, and heart rate
D-mode: time, heart rate, velocity, acceleration, trace, and RI
Software packages: abdomen, obstetric, small parts, gynecology, orthopedics, cardiology, peripheral vessels, and urology

Standard configurations:

DUS 60 main unit
12.1" TFT-LCD monitor
Two transducer connectors
256 frames cine loop memory
504MB built-in image storage
Two USB ports
Measurement & calculation software packages
Convex array transducer: C363UA (2.0/3.0/4.0/5.0/6.0MHz)

Options:

Linear array transducer: L743UA (6.0/7.0/8.0/9.0/10MHz)
Linear array transducer: L763UA (6.0/7.0/8.0/9.0/10MHz)
Convex array transducer: C343UA (2.0/3.0/4.0/5.0/6.0MHz)
Micro-convex array transducer: C321UA (2.0/3.0/4.0/5.0/6.0MHz)
Micro-convex array transducer: C613UA (4.5/5.5/6.5/7.5/8.5MHz)
Endorectal transducer: E743UA (6.0/7.0/8.0/9.0/10MHz)
Endovaginal transducer: E613UA (4.5/5.5/6.5/7.5/8.5MHz)
Needle-guided brackets for transducers
Video printer
Laser printer
DICOM3.0
Foot switch
Lithium battery
Mobile trolley
Hand carried bag

EDAN

www.edan.com.cn



DUS 60

Digital Ultrasonic Diagnostic Imaging System




ENG-US-DUS 60-V1.0-20100331



The DUS 60 is an impressive new compact ultrasound system, providing superb value and the best quality across the entire range of applications, with enhanced support of PW imaging to meet the higher diagnostic requirements.

> Powerful Technologies to Be Your Right Assistant

- > Complete Digital Beam Forming technologies achieve high quality imaging
- > THI and TSI technology present sharp and clear imaging accordingly
- > PW Doppler brings more clinical diagnostic values on vascular disease
- > 5-frequency broadband transducer selection for wide clinical applications including abdomen, obstetrics, small parts, gynecology, orthopedics, cardiology, peripheral vessels and urology



> Go Anywhere You Need to Go

- > Compact and lightweight design brings excellent mobility
- > 12.1" folding high resolution TFT-LCD screen generates image clarity
- > Built-in battery ready for scanning 2 hours at point-of-care



> Definite More Meaning on User-friendly

- > One touch image quality optimization by smart IP key
- > Rational-designed backlight palm controller
- > User-defined keys contribute smooth operation process
- > Quick-save key helps you the maximum patient throughput




> Feasible elements to enhance your confidence

- > Intelligent 8-segment TGC for precise adjustment
- > Multi-format data transferring via USB and DICOM
- > Multi-pseudo-color options for personalized needs



Liver




Thyroid



Fetal head



Kidney with pseudo-color



CCA PW with pseudo-color



CCA with pseudo-color